

PERFORMANCE DECLARATION

No. 3/2020 of 01.10.2020



Product type unique identification code: **Mass no. 5 (white clay-based) – Clinker cladding tile**

1.

Colours: Ice power (22), Grey eminence (23), Black stone (26), Vanilla sky (27), Pacific pearl (28), Just white (29), Caramel street (30), Cafe latte (31), Glacier cave (HF43), Arctic storm (HF44), Aztec ghost (HF45), Silver rose (HF46), Platinum skies (HF47), Astro house (HF48), Grey satin (HF49), Pearl satin (HF53), Roman theatre (HF54), Rusty moon (HF56), Kings valley (HF58), Summerian city (HF59), Desert land (HF60), Sand pepper (HF61), Iron rock (HF62), Rusty stone (HF63), White night (HF64), Night sound (HF65), Basalt river (HF66), Earth skin (HF67), Calm umber (HF68), Dance umber (HF69), Meteor veneer (HF70), Snow brick (HF71), Silver fox (HF72), Vestero's walls (HF73), Winter field (HF74). **Applicable to all formats on our offer.**

2.

Intended use(s):

For wall tiling (as finishing) in interiors and/or exteriors of building structures

3.

Manufacturer:

**Klinkier Przysucha S.A.
26 – 400 Przysucha
Skrzyńsko ul. Przemysłowa 56**

4.

Authorised representative: **Not applicable**

5.

Assessment and Verification of Constancy of Performance (AVCP) system(s) : **System 4**

6a.

Harmonised standard:

EN 14411:2012 „Ceramic tiles – Definition, classification, characteristics, assessment and verification of constancy of performance and marking” Annex C, Natural

6b.

Technical assessment body: **Not applicable**

Notified body (-ies): **Not applicable**

Declared performance

7.

General characteristics	Performance properties	Harmonized technical specification
Reaction to fire	class A1	EN 14411:2012
Water absorption	below 6%	
Thermal shock resistance	Yes	
External use durability	Yes	
External use durability: resistance to frosting - defrosting	Yes	
Dimension - Length and width	±2.0% to maximum ±4mm	
- Thickness - Squareness - Surface flatness - Curvature of sides	±10% ±1.0% ±1.5% ±1.0%	
Surface quality	Minimum 95% tiles should not have visible defects causing deterioration of the appearance of considerable surface of tiles.	

- masonry mortar

NPD

8. Relevant technical documentation or special technical documentation: **Not applicable**

Performance of the above specified product is in conformity with a set of performances declared. This performance declaration is issued in accordance with the Regulation (EU) no. 305/2011 at the exclusive liability of the above mentioned manufacturer.

Signed on behalf of the manufacturer by :

Sylwester Czuba

Head of Quality Control Department

KIEROWNIK
Działu Kontroli Jakości

mgr inż. Sylwester Czuba

Skrzyńsko 01.10.2020

.....
Place and date of issue

/-/ illegible signature

(signature)