

PERFORMANCE DECLARATION

No. 1/2023 of 19.05.2023



1.	<p>Product type unique identification code: Mass no. 1 (Red), mass no.2 (Brown). Clinker cladding tile</p> <p>Colours: Ruby red (01), Brown glazed (02), Natural brown (03), Wild wine (04), The secret garden (05), Note of cinnamon (06), Crimson island (07), Polar night (08), Sunny shore (09), Misty morning (12), Golden autumn (13), Tobacco leaf (14), Mahogany dream (15), The cherry orchard (16), Onyx black (17), Volcanic black (18), Ruby flame (19), Tibetan flame (20), Green valley (24), Green hills (25), Black pearl (32), Black diamond (33), Main street (34), Crimson tide (35), Black river (36), Black jack (37), Super black (38), Marrakesh dust (HF01), Bengali sunrise (HF02), Brick tower (HF03), Alhambra sun (HF04), Brick street (HF05), Bengali night (HF06), Old house (HF07), Deep purple (HF08), Tower bridge (HF09), Purple rain (HF10), Manor house (HF11), Red rock (HF12), Bastille wall (HF16), Red house (HF17), Dragon hill (HF18), Dark fortress (HF19), Monastic cellar (HF20), Aria rustica (HF21), Frozen island (HF22), African soul (HF23), Smooth jazz (HF24), Brazilian coffee (HF25), Chocolate tree (HF26), Blues shadow (HF27), Industrial revolution (HF28), Silesian story (HF29), Heart brick (HF30), Irish pub (HF31), Street life (HF32), Red hot (HF33), Small town (HF34), Winter palace (HF35), Royal stronghold (HF36), Wall street (HF37), Never land (HF38), Red square (HF39), Clay land (HF40), Gothic smile (HF41), Templarian treasure (HF42), Old factory (HF50), Old fort (HF51), Vintage town (HF52), Old cathedral (HF55), Old residence (HF57), Magic castle (HF75), Loft city (HF76), Dolomite peak (HF77), Stardust (HF78), Supernova (HF79), Antic city (HF80), Old Town (HF83), Castle forge (LF01), Valyria stone (LF02), Iron clay (LF03), Brick capital (LF04), Black heart (LF05), Argon wall (LF06), Old cathedral (LF07), Coral star (LF08), Asteroid house (LF09), Maghreb fire (LF10), Tibetan flame (LF11), Old amber (LF12), Brick republic (LF13), Castle rock (LF14), Another brick (LF15), Red zeppelin (LF16), King crimson (LF17), Obsidian shadow (LF18), Midnight dazzle (LF24)</p> <p>Applicable to all formats on our offer.</p>															
2.	<p>Intended use(s): For wall tiling (as finishing) in interiors and/or exteriors of building structures</p>															
3.	<p>Manufacturer: KING KLINKER S.A. 26 – 400 Przysucha Skrzyńsko ul. Przemysłowa 56</p>															
4.	<p>Authorised representative: Not applicable</p>															
5.	<p>Assessment and Verification of Constancy of Performance (AVCP) system(s) : System 4</p>															
6a.	<p>Harmonised standard: EN 14411:2012 „Ceramic tiles – Definition, classification, characteristics, assessment and verification of constancy of performance and marking” Annex C, Natural</p>															
6b.	<p>Technical assessment body: Not applicable Notified body (-ies): Not applicable</p>															
7.	<table border="1"> <thead> <tr> <th colspan="3" data-bbox="164 1496 1508 1556">Declared performance</th> </tr> <tr> <th data-bbox="164 1556 715 1691">General characteristics</th> <th data-bbox="715 1556 1214 1691">Performance properties</th> <th data-bbox="1214 1556 1508 1691">Harmonized technical specification</th> </tr> </thead> <tbody> <tr> <td data-bbox="164 1691 715 1751">Reaction to fire</td> <td data-bbox="715 1691 1214 1751">class A1</td> <td data-bbox="1214 1691 1508 1939" rowspan="3">EN 14411:2012</td> </tr> <tr> <td data-bbox="164 1751 715 1834">Water absorption</td> <td data-bbox="715 1751 1214 1834">~ 3%</td> </tr> <tr> <td data-bbox="164 1834 715 1939">Thermal shock resistance</td> <td data-bbox="715 1834 1214 1939">Yes</td> </tr> </tbody> </table>			Declared performance			General characteristics	Performance properties	Harmonized technical specification	Reaction to fire	class A1	EN 14411:2012	Water absorption	~ 3%	Thermal shock resistance	Yes
Declared performance																
General characteristics	Performance properties	Harmonized technical specification														
Reaction to fire	class A1	EN 14411:2012														
Water absorption	~ 3%															
Thermal shock resistance	Yes															

7.	External use durability	Yes	EN 14411:2012
	External use durability: resistance to frosting - defrosting	Yes	
	Dimension - Length and width - Thickness - Squareness - Surface flatness - Curvature of sides	$\pm 2.0\%$ to maximum $\pm 4\text{mm}$ $\pm 10\%$ $\pm 1.0\%$ $\pm 1.5\%$ $\pm 1.0\%$	
	Surface quality	Minimum 95% tiles should not have visible defects causing deterioration of the appearance of considerable surface of tiles.	
	Bonding strength / adhesion - cement adhesives - dispersion adhesives - reactive resin adhesive - masonry mortar	NPD NPD NPD NPD	

8. Relevant technical documentation or special technical documentation: **Not applicable**

Performance of the above specified product is in conformity with a set of performances declared. This performance declaration is issued in accordance with the Regulation (EU) no. 305/2011 at the exclusive liability of the above mentioned manufacturer.

Skrzyńsko 19.05.2023

.....

Place and date of issue

Signed on behalf of the manufacturer by :
Sylwester Czubak
Head of Quality Control Department
Działu Kontroli Jakości

mgr inż. Sylwester Czubak
/-/ illegible signature
(signature)