

**PERFORMANCE DECLARATION**

**No. 3/2023 of 19.05.2023**



Product type unique identification code: **Mass no. 5 (white clay-based) – Clinker cladding tile**

1. **Colours:** Ice power (22), Grey eminence (23), Black stone (26), Vanilla sky (27), Pacific pearl (28), Just white (29), Caramel street (30), Cafe latte (31), Glacier cave (HF43), Arctic storm (HF44), Aztec ghost (HF45), Silver rose (HF46), Platinum skies (HF47), Astro house (HF48), Grey satin (HF49), Pearl satin (HF53), Roman theatre (HF54), Rusty moon (HF56), Kings valley (HF58), Summerian city (HF59), Desert land (HF60), Sand pepper (HF61), Iron rock (HF62), Rusty stone (HF63), White night (HF64), Night sound (HF65), Basalt river (HF66), Earth skin (HF67), Calm umber (HF68), Dance umber (HF69), Meteor veneer (HF70), Snow brick (HF71), Silver fox (HF72), Vestero's walls (HF73), Winter field (HF74), Steel rebel (HF81), Volcanic wall (HF82), Silver stone (LF19), Moon river (LF20), Grey land (LF21), Dolomite brick (LF22), Golden grey (LF 23).  
**Applicable to all formats on our offer.**

2. Intended use(s):  
**For wall tiling (as finishing) in interiors and/or exteriors of building structures**

3. Manufacturer:  
**KING KLINKER S.A.  
26 – 400 Przysucha  
Skrzyńsko ul. Przemysłowa 56**

4. Authorised representative: **Not applicable**

5. Assessment and Verification of Constancy of Performance (AVCP) system(s) : **System 4**

6a. Harmonised standard:  
**EN 14411:2012 „Ceramic tiles – Definition, classification, characteristics, assessment and verification of constancy of performance and marking” Annex C, Natural**

6b. Technical assessment body: **Not applicable**  
Notified body (-ies): **Not applicable**

**Declared performance**

	<b>General characteristics</b>	<b>Performance properties</b>	<b>Harmonized technical specification</b>
7.	<b>Reaction to fire</b>	class A1	<b>EN 14411:2012</b>
	<b>Water absorption</b>	below 6%	
	<b>Thermal shock resistance</b>	Yes	
	<b>External use durability</b>	Yes	
	<b>External use durability: resistance to frosting - defrosting</b>	Yes	
	<b>Dimension</b>		
	- Length and width	±2.0% to maximum ±4mm	
- Thickness	±10%		
- Squareness	±1.0%		
- Surface flatness	±1.5%		
- Curvature of sides	±1.0%		

7.	<b>Surface quality</b>	Minimum 95% tiles should not have visible defects causing deterioration of the appearance of considerable surface of tiles.	EN 14411:2012
	<b>Bonding strength / adhesion</b> - cement adhesives - dispersion adhesives - reactive resin adhesive - masonry mortar	NPD NPD NPD NPD	
8.	Relevant technical documentation or special technical documentation: <b>Not applicable</b>		
<p>Performance of the above specified product is in conformity with a set of performances declared. This performance declaration is issued in accordance with the Regulation (EU) no. 305/2011 at the exclusive liability of the above mentioned manufacturer.</p> <p>Signed on behalf of the manufacturer by :</p> <p><b>Sylwester Czubak</b>  Head of Quality Control Department  Działu Kontroli Jakości</p> <p>KIEROWNIK</p> <p><i>mgr inż. Sylwester Czubak</i>  /-/ illegible signature  (signature)</p> <p>Skrzyńsko 19.05.2023  .....  Place and date of issue</p>			